



EcoScreen Floor

ABSORPTION

PRODUCT CHARACTERISTICS

EcoScreen Floor are mobile partitions that allow you to freely divide the office space. They allow you to separate individual workstations or groups of workstations, separate the employee area from the communication path, or create a special relaxation zone or conversation zone. EcoScreen walls can be connected to each other in any way with special connectors, so you can change the office layout at any time.

EcoScreen Floor provides visual separation of individual workstations and creates an appropriate level of privacy for employees. In particular, they provide excellent sound insulation. The texture of the material resembles natural wool, which makes any interior warm and cozy.

The minimalist look of the screens makes them universal and timeless. Rounded corners give them additional

lightness and elegance. For high walls, it is possible to add a perforated pattern on the top edge of the screen to facilitate eye contact between stations.

EcoScreen Floor

ABSORPTION







MATERIAL

EcoScreen Floor is made of compressed polyester fibers recovered in the recycling process of PET bottles. They are resistant to mechanical damage and deformation. The material is friendly to the environment and human health. Unlike mineral wool, it does not produce dust, is environmentally friendly and protects human health. The product is fully recyclable. It is odorless, mold resistant and does not emit toxic substances. This innovative material has very good soundproofing properties of class A, while providing high rigidity and acoustic insulation. It has a high class of non-flammability. In addition to its acoustic and decorative properties, it can also be used as a pinboard for photos, drawings and notes with pins.



WŁAŚCIWOŚCI PRODUKTU

	ABSORPTION COEFFICIENT	≥ 0,85
	ABSORPTION CLASS	B
	FIRE CLASSIFICATION	B, s1, d0
	INSULATION	high
	ANTISTATIC	yes
	ASSEMBLY	free-standing
	REACTION TO UV RAYS	no discoloration
	ECOLOGICAL PRODUCT	yes

INSTALLATION


Panels of the free-standing version are mounted on metal feet.



TECHNICAL DRAWINGS


PANEL THICKNESS:

9 mm, 15 mm




Feet for free-standing panels


SAMPLE PATTERNS




NES CR2




NES D1



NES SD1



NES CU1



Lubimy wyzwania, podaj kształt i wymiary których potrzebujesz

THE CURRENT CATALOG OF AVAILABLE DESIGNS:

- Nyquista EcoScreen Collection_2020 ENG.pdf
- Nyquista EcoScreen Collection_2020 PL.pdf